


SCHEDA TECNICA TESSUTO (FABRIC SPECIFICATIONS)

| | |
|--------------------|--------------|
| NOME (NAME) | TERES |
|--------------------|--------------|

| | METODO (METHOD) | VALORI (VALUE) |
|--|--|-----------------------|
| COMPOSIZIONE (COMPOSITION) | LEGGE (LAW) 883 | 40%CO 42%VI 18%WO |
| ALTEZZA (WIDTH) | UNI EN 1773:1998 | 140 cm |
| PESO (WEIGHT) | UNI 5114:1982 | 529 g/m ² |
| MARTINDALE | UNI EN ISO 12947-2:2000 | 32.000 giri (turns) |
| PILLING TEST | UNI EN ISO 12945-2:2002 5000 CYCLES | 5 |
| SOLIDITA' ALLA LUCE (COLOURFASTNESS TO LIGHT) | UNI EN ISO 105-B02:2001 | 5/6 |
| SOLIDITA' ALLO SFREGAMENTO (COLOURFASTNESS TO CROCKING) – SECCO (DRY) | UNI EN ISO 105-X12:2003 | 5 |
| SOLIDITA' ALLO SFREGAMENTO (COLOURFASTNESS TO CROCKING) – UMIDO (WET) | UNI EN ISO 105-X12:2003 | 5 |

| |
|---|
| MANUTENZIONE (CLEANING) |
|  |

L'articolo sopra descritto è conforme alle norme R.E.A.C.H. 1907/2006/CE
The item above described comply with the norms R.E.A.C.H. 1907/2006/CE

Compilato da QUA – Emiss. 20/02/09 Rev.0 - Sigla *OP*